

Easyfitshutter Kit: MEASURING GUIDE

Width

Measure the width of your window inside the recess in three places: across the bottom, middle and top of the window. Take the smallest measurement. (10mm will be deducted by opennshut.co.uk from your window width and height to allow a 5mm shadow gap all round).

Height

Measure the height of your window inside the recess in three places: down the left hand side, middle (centre) and right hand side of the window. Take the smallest measurement. For shutters that only go halfway up the window, measure from the windows sill to top of where you would like the shutters to finish. (10mm will be deducted by opennshut.co.uk from your window width and height to allow a 5mm shadow gap all round)

Top opening or horizontal rail:

Top opening: Measure from the window sill up to the top point where you would like the shutters to open. If the window has a horizontal rail, I would recommend lining-up the bottom set of shutters to the highest point on the window rail.

Horizontal rail: Measure from the window sill to the middle point where you would like a horizontal rail. If the window has a horizontal rail, I would recommend lining-up the middle rail of the shutters to the rail of the window.

Can you handle it:

Measure from the front of the handle to the point on the window frame where you are fitting the shutter frame. You can choose from 3 sizes of outer frames in which the shutters fit. Small, Medium and Large. The table below will ensure the correct frame is chosen for the size handle you have.

Standard	Small louvre (47mm)	Medium louvre (64mm)	Large louvre (89mm)
Small frame (46mm)	8mm	0mm	-13mm
Medium frame (60mm)	22mm	13mm	1mm
Large frame (76mm)	38mm	29mm	17mm

Elite	Small louvre (47mm)	Medium lowre (64mm)	Large louvre (89mm)
Small frame (50mm)	10mm	1mm	-12mm
Medium frame (64mm)	23mm	14mm	2mm
Large frame (76mm)	35mm	27mm	14mm

Battens:

Measure how much clearance you require from the back edge of the shutter frame to the window frame. Chose between small (40mm), medium (50mm) and large (60mm) deep battens. All the battens are 30mm wide, allowing for the shadow gap clearance, you will have 25mm on which to fix your shutter frame.